



FX & VFX Series International

Sealed & Vented True Sinewave Inverter/Charger

Sealed FX

- Sinewave Output
- Intelligent Battery Charging
- Modular Stackable Design
- High Operating Efficiency
- Weather-resistant Sealed Chassis
- Field Serviceable
- Integrated Network Communications
- Standard 5 Year Warranty

Vented VFX

- Sinewave Output
- Intelligent Battery Charging
- Modular Stackable Design
- High Operating Efficiency
- Bug Proof Chassis
- Corrosion Resistant Internal Components
- Field Serviceable
- Integrated Network Communications
- Standard 5 Year Warranty



Vented VFX

Sealed FX



OutBack Power's true sinewave inverter/charger is a complete power solution. It incorporates a DC-to-AC sinewave inverter, battery charger and an AC transfer relay housed within a die-cast aluminum chassis. Intelligent multistage battery charging reduces generator run-time and prolongs the life of your batteries. Built-in networked communications enables multiple units to be stacked and connected with other OutBack power electronics providing industry leading integration and near infinite application flexibility. The exclusive modular system architecture means that increased power output is just an additional inverter/charger away.

Our flagship FX series uses a sealed chassis that can operate in the harshest environmental conditions such as areas with high humidity, corrosive salt air, sand or dust. The VFX series uses a vented chassis with bug proof screened openings that allow high output AC power in the hottest of operating conditions.

OutBack Power Inverter/Chargers are the only choice when you need a true sinewave, powerful, modular and reliable power solution for your home, business or extreme application.

OutBack
POWER
member of The  Group™

www.outbackpower.com

FX & VFX Series International Specifications

		Sealed Models			Vented Models		
		FX2012ET	FX2024ET	FX2348ET	VFX2612E	VFX3024E	VFX3048E
Nominal DC Input Voltage		12 VDC	24 VDC	48 VDC	12 VDC	24 VDC	48 VDC
Continuous Power Rating at 25°C (77°F)		2000 VA	2000 VA	2300 VA	2600 VA	3000 VA	3000 VA
AC Voltage/Frequency		230 VAC / 50 Hz	230 VAC / 50 Hz	230 VAC / 50 Hz	230 VAC / 50 Hz	230 VAC / 50 Hz	230 VAC / 50 Hz
Continuous AC RMS Output at 25°C (77°F)		8.7 Amps AC	8.7 Amps AC	10 Amps AC	11.3 Amps AC	13 Amps AC	13 Amps AC
Idle Power	Full	~ 20 Watts	~ 20 Watts	~ 23 Watts	~ 20 Watts	~ 20 Watts	~ 23 Watts
	Search	~ 6 Watts	~ 6 Watts	~ 6 Watts	~ 6 Watts	~ 6 Watts	~ 6 Watts
Typical Efficiency		90%	92%	93%	90%	92%	93%
Total Harmonic Distortion	Typical	2%	2%	2%	2%	2%	2%
	Maximum	5%	5%	5%	5%	5%	5%
Output Voltage Regulation		± 2%	± 2%	± 2%	± 2%	± 2%	± 2%
Maximum Output Current	Peak	28 Amps AC	35 Amps AC	35 Amps AC	28 Amps AC	35 Amps AC	35 Amps AC
	RMS	20 Amps AC	25 Amps AC	25 Amps AC	20 Amps AC	25 Amps AC	25 Amps AC
AC Overload Capability	Surge	4600 VA	5750 VA	5750 VA	4600 VA	5750 VA	5750 VA
	5 Seconds	4000 VA	4800 VA	4800 VA	4000 VA	4800 VA	4800 VA
	30 Minutes	2500 VA	3100 VA	3100 VA	3100 VA	3300 VA	3300 VA
AC Input Current Maximum		30 Amps AC	30 Amps AC	30 Amps AC	30 Amps AC	30 Amps AC	30 Amps AC
AC Input Voltage Range (MATE Adjustable)		160 to 300 VAC	160 to 300 VAC	160 to 300 VAC	160 to 300 VAC	160 to 300 VAC	160 to 300 VAC
AC Input Frequency Range		44 to 56 Hz	44 to 56 Hz	44 to 56 Hz	44 to 56 Hz	44 to 56 Hz	44 to 56 Hz
DC Input Voltage Range		10.5 to 17 VDC	21 to 34 VDC	42 to 68 VDC	10.5 to 17 VDC	21 to 34 VDC	42 to 68 VDC
Continous Battery Charge Output		100 Amps DC	55 Amps DC	35 Amps DC	120 Amps DC	85 Amps DC	45 Amps DC
Temperature Range	Rated	0 to 50°C (power derated above 25°C)			0 to 50°C (power derated above 25°C)		
	Maximum	-25 to 60°C (Functions, but does not necessarily meet all component specifications)			-25 to 60°C (Functions, but does not necessarily meet all component specifications)		
Warranty		Standard 5 year Warranty			Standard 5 year Warranty		
Weight	Unit	29 kg (62 lbs)			28 kg (61 lbs)		
	Shipping	31 kg (67 lbs)			31 kg (67 lbs)		
Dimensions (H x W x L)	Unit	33 x 21 x 41 cm (13 x 8.24 x 16.25")			30 x 21 x 41 cm (12 x 8.25 x 16.25")		
	Shipping	55 x 33 x 56 cm (21.75 x 13 x 22")			55 x 33 x 56 cm (21.75 x 13 x 22")		

Available From:

